



United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.usplo.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO
09/895,788	06/29/2001	Thomas L. Stachura	42390P10773	5580
8791	7590 09/29/2005		EXAM	INER
	SOKOLOFF TAYLO	SHIFERAW, ELENI A		
12400 WILSHIRE BOULEVARD SEVENTH FLOOR LOS ANGELES, CA 90025-1030			ART UNIT	PAPER NUMBER
			2136	

DATE MAILED: 09/29/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

h						
	Application No.	Applicant(s)				
Office Action Summany	09/895,788 😁	STACHURA ET AL.				
Office Action Summary	Examiner	Art Unit				
The MANUALC DATE of this communication and	Eleni A. Shiferaw	2136				
The MAILING DATE of this communication app Period for Reply	ears on the cover sheet with the c	orrespondence address				
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING DA - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period w - Failure to reply within the set or extended period for reply will, by statute, Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 16(a). In no event, however, may a reply be tim ill apply and will expire SIX (6) MONTHS from cause the application to become ABANDONEI	I. lely filed the mailing date of this communication. O (35 U.S.C. § 133).				
Status						
1) Responsive to communication(s) filed on 14 July 2005.						
2a) ☐ This action is FINAL . 2b) ☑ This	action is non-final.					
•	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.					
Disposition of Claims						
4)⊠ Claim(s) <u>1-5,7,8,10-12,14-17,19-21,23-28 and 30-39</u> is/are pending in the application.						
4a) Of the above claim(s) 6,9,13,18,22 and 29 is/are withdrawn from consideration.						
·	5) Claim(s) is/are allowed.					
	,					
	7) Claim(s) is/are objected to.					
8) Claim(s) are subject to restriction and/or election requirement.						
Application Papers						
9) The specification is objected to by the Examiner.						
10)⊠ The drawing(s) filed on 11 October 2001 is/are: a)⊠ accepted or b)□ objected to by the Examiner.						
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a). Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).						
11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.						
Priority under 35 U.S.C. § 119						
12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of:						
1. Certified copies of the priority documents have been received.						
 2. Certified copies of the priority documents have been received in Application No 3. Copies of the certified copies of the priority documents have been received in this National Stage 						
3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).						
* See the attached detailed Office action for a list of the certified copies not received.						
	·					
Attachment(s)						
1) Notice of References Cited (PTO-892) 4) Interview Summary (PTO-413)						
Notice of Draftsperson's Patent Drawing Review (PTO-948) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08) Paper No(s)/Mail Date	Paper No(s)/Mail Da 5) Notice of Informal P 6) Other:	atent Application (PTO-152)				

Art Unit: 2136

Detailed Action

1. The request filed July 19, 2005 for a Request for Continued Examination (RCE) under 37 CFR 1.114 based on parent Application 09895788 is acceptable and RCE has been established. Claims 1-5, 7-8, 10-12, 14-17, 19-21, 23-28, and 30-35 are pending. Claims 36-39 have been added. Claims 30 and 32 have been amended. Claims 1-5, 7-8, 10-12, 14-17, 19-21, 23-28, 30-35 and 36-39 are now presented for examination.

Claim Rejections - 35 USC § 102

2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.
- 3. Claims 1-4, 31-32, 36-37, and 39 are rejected under 35 U.S.C. 102(e) as being anticipated by Gambino (Patent No.: US 6,339,796 B1).

As per claim 1 and 31, Gambino discloses a method comprising:

establishing secured communication between a client device and server device; wherein communication is secured using, at least in part, synchronized security sequence value(s) (col. 3 lines 32-37 and lines 55-59, and col. 7 lines 13-21; data host/first data processing system (12) and remote system/second data processing system (16) are synchronized using sequence numbers);

Art Unit: 2136

storing a security sequence value as a resynchronization value (col. 4 lines 24-41; periodically storing/refreshing sequence numbers for recovery of system failure and/or for resynchronization request);

detecting at least one event desynchronizing said secured communication (col. 4 lines 34-37 and claim 1 lines 6-20; de-synchronization/failure of data host is detected); and

requesting resynchronization of security sequence values, comprising sending at least a representation of said resynchronization value from said client device to said server device (col. 2 lines 33-37, col. 5 lines 1-5, and claim 1 lines 26-29; data host (12) sending status request message packet/resynchronization request that includes sequence number stored on external device of the data host (12)).

As per claim 2, Gambino teaches the method, further comprising performing anti-replay filtering using said security sequence values (col. 4 lines 54-58; discarding duplicate sequence numbers...).

As per claim 3, Gambino teaches the method, wherein sending at least a representation of said resynchronization value includes embedding said resynchronization value in at least one header and/or at least one payload of a data packet (col. 4 lines 45-50; a header transport/THDR containing sequence number...).

As per claims 4 and 32, Gambino teaches the method/medium, wherein said storing a client resynchronization value includes periodically refreshing a stored value with a new

Art Unit: 2136

value at a selected interval from security sequence values already used in a secured communication session (col. 4 lines 24-41).

As per claim 36, Gambino teaches the method, further comprising receiving a response to the resynchronization request, the response including the resynchronization value (col. 5 lines 5-7).

As per claim 37, Gambino teaches the method, wherein the resynchronization value is contained in payload data of the response (col. 5 lines 5-7; replay pocket header/a transport header/THDR that includes sequence number of the remote system...).

As per claim 39, Gambino teaches the method, further comprising resynchronizing the secured communication using the resynchronization value and the second resynchronization value (claim 13 lines 47-col. 12 lines 12; the resynchronization value sent from data host (12) and resynchronization value replied from remote system is used for resynchronization).

Claim Rejections - 35 USC § 103

4. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Art Unit: 2136

5. Claims 5, 7-8, 10-12, 14-17, 19-21, 23-28, 30, 33-35, and 38 are rejected under 35 U.S.C. 103(a) as being unpatentable over Gambino (Patent No.: US 6,339,796 B1) in view of Johnson et al. (Johnson, Patent No.: US 6,247,059 B1).

As per claim 5, Gambino discloses the method comprising:

establishing secured communication between a client device and server device; wherein communication is secured using, at least in part, a plurality of synchronized security sequence values (col. 3 lines 32-37 and lines 55-59, and col. 7 lines 13-21; data host/first data processing system (12) and remote system/second data processing system (16) are synchronized using sequence numbers);

receiving a request for resynchronization from the client device, the request including at least a representation of a client resynchronization value, the client resynchronization value being a stored synchronized security value of the plurality of synchronized security sequence values (col. 2 lines 33-46, col. 5 lines 5-7 and col. 4 lines 24-41; remote device (16) receives the resynchronization request from data host (12), wherein the request message includes sequence number/resynchronization value that is stored on external memory of data host for resynchronization);

acknowledging the client request for resynchronization (col. 2 lines 39-46 and claim 1 lines 30-34; acknowledgment response including the remote system resynchronization value is sent to data host to reestablish communication); and

reestablishing secured communication using said client resynchronization value and said server resynchronization value (claim 1 lines 35-38, and col. 6 lines 37-46; communication is reestablished).

Art Unit: 2136

Gambino discloses all the subject matter as described above. Gambino reestablishes the communication by sending a replay message, for the resynchronization request, that includes remote system's resynchronization value. Gambino does not explicitly teach that the replay message including resynchronization value sent from data host.

However Johnson discloses an acknowledging comprising sending the representation of resynchronization value and at least a representation of a server resynchronization value from said server device to said client device (Johnson col. 2 lines 18-60; establishing communication and exchanging multicast message between sender node and receiver node. The multicast message is structured to include a sequence number. When a node fails or sequence number is out of order a resynchronization request is sent from receiver node to sender node and the sender node acknowledges by sending its new marker/server resynchronization value and the sequence number of the last multicast message unacknowledged by the receiving node/negative acknowledgment multicast messages, messages receiver node has not received, sent from receiver node/resynchronization value).

Therefore it would have been obvious to one having ordinary skill in the art at the time of the invention was made to employ the teachings of Johnson within the system of Gambino because they are analogous in multi-computer synchronization and resynchronization method. One would have been motivated to incorporate resynchronization value of the requester along with resynchronization value of the server on acknowledgment/replay message for resynchronization request received because it is well known in the art to include the requester resynchronization value. And also it would

Art Unit: 2136

verify that the receiver is the right device that the requester intended to be resynchronized with.

As per claim 14, Gambino discloses an apparatus, comprising;

- (a) a security interface to engage in secured communication with at least one network node, wherein said security interface and said at least one network node use synchronized security sequence values at least in part to authenticate said secured communication (col. 3 lines 32-37 and lines 55-59, and col. 7 lines 13-21; data host/first data processing system (12) and remote system/second data processing system (16) are synchronized using sequence numbers);
- (i) a recorder to store at least one security sequence value (col. 4 lines 24-41; periodically storing/refreshing sequence numbers for recovery of system failure and/or for resynchronization request);
- (ii) a desynchronization detector coupled to said security interface (col. 4 lines 34-37 and claim 1 lines 6-20; de-synchronization/failure of data host is detected by detector of data host (12));
- (iii) a resynchronization requester to send the stored security sequence value to at least one network node after a desynchronization (col. 2 lines 33-37, col. 5 lines 1-5, and claim 1 lines 26-29; data host (12) sending status request message packet/resynchronization request that includes sequence number stored on external device of the data host (12)); and
- (iv) a verifier to receive feedback from said at least one network node (claim 13 lines 47-col. 12 lines 12);

Art Unit: 2136

- (b) a security agent coupled to said at least one network node, comprising:
- (i) a request receiver to recognize said stored security sequence value (col. 7 lines 52-65; remote system, that recognizes the stored sequence values, receives the resynchronization request sent from data host (12) and replies to the request for resynchronization); and
- (ii) an acknowledger to send said feedback from said security agent to said security interface; said feedback comprising a node security sequence value from said network node (col. 2 lines 39-46 and claim 1 lines 30-34; acknowledgment response including the remote system resynchronization value is sent to data host to reestablish communication from acknowledger remote system).

Gambino discloses all the subject matter as described above. Gambino reestablishes the communication by sending a replay message, for the resynchronization request, that includes remote system's resynchronization value. Gambino does not explicitly teach that the replay message including resynchronization value sent from data host.

However Johnson discloses a feedback comprising requester's sequence value (Johnson col. 2 lines 18-60; establishing communication and exchanging multicast message between sender node and receiver node. The multicast message is structured to include a sequence number. When a node fails or sequence number is out of order a resynchronization request is sent from receiver node to sender node and the sender node acknowledges by sending its new marker/server resynchronization value and the sequence number of the last multicast message unacknowledged by the receiving

Art Unit: 2136

node/negative acknowledgment multicast messages, messages receiver node has not received, sent from receiver node/resynchronization value).

Therefore it would have been obvious to one having ordinary skill in the art at the time of the invention was made to employ the teachings of Johnson within the system of Gambino because they are analogous in multi-computer synchronization and resynchronization method. One would have been motivated to incorporate resynchronization value of the requester along with resynchronization value of the server on acknowledgment/replay message for resynchronization request received because it is well known in the art to include the requester resynchronization value. And also it would verify that the receiver is the right device that the requester intended to be resynchronized with.

As per claim 17, Gambino discloses a computer network security sequence value resynchronizer, comprising:

- (a) a sender having at least access to a nonvolatile random access memory (col. 4 lines 24-41; data host has access to periodically stored sequence numbers for recovery of system failure and/or for resynchronization request);
- (b) said sender to transmit a data packet containing at least in part a stored sender resynchronization value from said nonvolatile random access memory over said computer network (col. 2 lines 33-37, col. 5 lines 1-5, and claim 1 lines 26-29; data host (12) sending status request message packet/resynchronization request that includes sequence number stored on external device of the data host (12)); and

Art Unit: 2136

(c) an acknowledger connected to said computer network to receive said sender resynchronization value from said sender (col. 2 lines 39-46 and claim 1 lines 30-34; acknowledger remote system receives requests and returns acknowledgment response including the remote system resynchronization value);

Gambino discloses all the subject matter as described above. Gambino reestablishes the communication by sending a replay message, for the resynchronization request, that includes remote system's resynchronization value. Gambino does not explicitly teach that the replay message including resynchronization value sent from data host.

However Johnson discloses a said acknowledger returning said sender resynchronization value to said sender as security assurance (Johnson col. 2 lines 18-60; establishing communication and exchanging multicast message between sender node and receiver node. The multicast message is structured to include a sequence number. When a node fails or sequence number is out of order a resynchronization request is sent from receiver node to sender node and the sender node acknowledges by sending its new marker/server resynchronization value and the sequence number of the last multicast message unacknowledged by the receiving node/negative acknowledgment multicast messages, messages receiver node has not received, sent from receiver node/resynchronization value).

Therefore it would have been obvious to one having ordinary skill in the art at the time of the invention was made to employ the teachings of Johnson within the system of Gambino because they are analogous in multi-computer synchronization and resynchronization method. One would have been motivated to incorporate

Page 11

resynchronization value of the requester along with resynchronization value of the server on acknowledgment/replay message for resynchronization request received because it is well known in the art to include the requester resynchronization value. And also it would verify that the receiver is the right device that the requester intended to be resynchronized with.

As per claim 20, Gambino disclose a method comprising:

establishing secured communication between a security interface and a network node, said security interface to resynchronize security sequence values between said security interface and said network node (col. 3 lines 32-37 and lines 55-59, and col. 7 lines 13-21; data host/first data processing system (12) and remote system/second data processing system (16) are synchronized using sequence numbers),

storing a first resynchronization value selected by said security interface (col. 4 lines 24-41; periodically storing/refreshing sequence numbers for recovery of system failure and/or for resynchronization request); and

resynchronizing said security sequence values after a break in said secured communication (claim 1 lines 35-38, and col. 6 lines 37-46; communication is reestablished), said resynchronizing further comprising:

sending said first resynchronization value from said security interface to said network node (col. 2 lines 33-37, col. 5 lines 1-5, and claim 1 lines 26-29; data host (12) sending status request message packet/resynchronization request that includes sequence number stored on external device of the data host (12));

Art Unit: 2136

sending said a second resynchronization value from said network node to said security interface (col. 2 lines 39-46 and claim 1 lines 30-34; acknowledgment response including the remote system resynchronization value is sent to data host to reestablish communication); and

reestablishing said secured communication using said first resynchronization value and said second resynchronization value (claim 1 lines 35-38, and col. 6 lines 37-46; communication is reestablished using the data host resynchronization value sent from data host and resynchronization value received from remote system).

Gambino discloses all the subject matter as described above. Gambino reestablishes the communication by sending a replay message, for the resynchronization request, that includes remote system's resynchronization value. Gambino does not explicitly teach sending said first resynchronization value from said network node to said security interface (the replay message including resynchronization value sent from data host).

However Johnson discloses sending said first resynchronization value from said network node to said security interface (Johnson col. 2 lines 18-60; establishing communication and exchanging multicast message between sender node and receiver node. The multicast message is structured to include a sequence number. When a node fails or sequence number is out of order a resynchronization request is sent from receiver node to sender node and the sender node acknowledges by sending its new marker/server resynchronization value and the sequence number of the last multicast message unacknowledged by the receiving node/negative acknowledgment multicast messages,

messages receiver node has not received, sent from receiver node/resynchronization value).

Therefore it would have been obvious to one having ordinary skill in the art at the time of the invention was made to employ the teachings of Johnson within the system of Gambino because they are analogous in multi-computer synchronization and resynchronization method. One would have been motivated to incorporate resynchronization value of the requester along with resynchronization value of the server on acknowledgment/replay message for resynchronization request received because it is well known in the art to include the requester resynchronization value. And also it would verify that the receiver is the right device that the requester intended to be resynchronized with.

As per claim 28, Gambino discloses a method, comprising:

establishing secured communication between a server device and a client device, said secured communication using server security sequence values synchronized with client security sequence values (col. 3 lines 32-37 and lines 55-59, and col. 7 lines 13-21; data host/first data processing system (12) and remote system/second data processing system (16) are synchronized using sequence numbers);

saved client security sequence value in nonvolatile memory as a saved client security sequence value (col. 4 lines 24-41; periodically storing/refreshing sequence numbers for recovery of system failure and/or for resynchronization request); and

Art Unit: 2136

resynchronizing server and client security sequence values after a desynchronization event, resynchronizing including sending said saved client security sequence value from said nonvolatile memory to said server device (col. 2 lines 33-37, col. 5 lines 1-5, and claim 1 lines 26-29; data host (12) sending status request message packet/resynchronization request that includes sequence number stored on external device of the data host (12)), and returning server security sequence value (col. 2 lines 39-46 and claim 1 lines 30-34; response including the remote system/server resynchronization value is sent to data host to reestablish communication);

Gambino discloses all the subject matter as described above. Gambino reestablishes the communication by sending a replay message, for the resynchronization request, that includes remote system's resynchronization value. Gambino does not explicitly teach returning said saved client security sequence value from said server device to said client device in a data packet (the replay message including resynchronization value sent from data host).

However Johnson discloses returning said saved client security sequence value from said server device to said client device in a data packet (Johnson col. 2 lines 18-60; establishing communication and exchanging multicast message between sender node and receiver node. The multicast message is structured to include a sequence number. When a node fails or sequence number is out of order a resynchronization request is sent from receiver node to sender node and the sender node acknowledges by sending its new marker/server resynchronization value and the sequence number of the last multicast message unacknowledged by the receiving node/negative acknowledgment multicast

Art Unit: 2136

messages, messages receiver node has not received, sent from receiver node/resynchronization value).

Therefore it would have been obvious to one having ordinary skill in the art at the time of the invention was made to employ the teachings of Johnson within the system of Gambino because they are analogous in multi-computer synchronization and resynchronization method. One would have been motivated to incorporate resynchronization value of the requester along with resynchronization value of the server on acknowledgment/replay message for resynchronization request received because it is well known in the art to include the requester resynchronization value. And also it would verify that the receiver is the right device that the requester intended to be resynchronized with.

As per claim 33, Gambino teaches a machine-readable medium having stored thereon data representing sequences of instructions that, when executed by a processor, cause the processor to perform operations comprising:

establishing secured communication between a client device and server device (col. 3 lines 32-37); wherein communication is secured using, at least in part a plurality of synchronized security sequence values (col. 3 lines 32-37 and lines 55-59, and col. 7 lines 13-21; data host/first data processing system (12) and remote system/second data processing system (16) are synchronized using sequence numbers);

receiving a request for resynchronization from the client device, the request including a resynchronization value, the resynchronization value being a stored synchronized security sequence of the plurality of security

Art Unit: 2136

sequence values (col. 2 lines 33-46, col. 5 lines 5-7 and col. 4 lines 24-41; remote device (16) receives the resynchronization request from data host (12), wherein the request message includes sequence number/resynchronization value that is stored on external memory of data host for resynchronization);

acknowledging the client request for resynchronization, acknowledging comprising sending a server resynchronization value from the server device to the client device (col. 2 lines 39-46 and claim 1 lines 30-34; acknowledgment response including the remote system resynchronization value is sent to data host to reestablish communication); and

reestablishing secured communication using the client resynchronization value and the server resynchronization value (claim 1 lines 35-38, and col. 6 lines 37-46; communication is reestablished using the data host resynchronization value sent from data host and resynchronization value received from remote system).

Gambino discloses all the subject matter as described above. Gambino reestablishes the communication by sending a replay message, for the resynchronization request, that includes remote system's resynchronization value. Gambino does not explicitly teach acknowledging comprising sending resynchronization value from the server device to the client device (the replay message including resynchronization value sent from data host).

However Johnson discloses acknowledging comprising sending resynchronization value from the server device to the client device (Johnson col. 2 lines 18-60; establishing communication and exchanging multicast message between sender node and receiver node. The multicast message is structured to include a sequence number. When a node

Art Unit: 2136

fails or sequence number is out of order a resynchronization request is sent from receiver node to sender node and the sender node acknowledges by sending its new marker/server resynchronization value and the sequence number of the last multicast message unacknowledged by the receiving node/negative acknowledgment multicast messages, messages receiver node has not received, sent from receiver node/resynchronization value).

Therefore it would have been obvious to one having ordinary skill in the art at the time of the invention was made to employ the teachings of Johnson within the system of Gambino because they are analogous in multi-computer synchronization and resynchronization method. One would have been motivated to incorporate resynchronization value of the requester along with resynchronization value of the server on acknowledgment/replay message for resynchronization request received because it is well known in the art to include the requester resynchronization value. And also it would verify that the receiver is the right device that the requester intended to be resynchronized with.

As per claim 7, Gambino and Johnson disclose all the subject matter as described above. In addition Gambino discloses the method, wherein sending at least a representation of said client and said server resynchronization values includes embedding said client and said server resynchronization values in at least one header and/or at least one payload of a data packet that conforms to IPsec standards (col. 4 lines 45-50 and col. 3 lines 60-67; a header transport/THDR containing sequence number...RTP).

As per claims 8 and 21, Gambino and Johnson disclose all the subject matter as described above. In addition Gambino discloses the method, further comprising performing said method using a state machine in network circuitry (col. 4 lines 24-41).

As per claim 10, Gambino and Johnson disclose all the subject matter as described above. In addition Gambino discloses the method, further comprising performing anti-replay filtering using said synchronized security sequence values (col. 4 lines 54-58; discarding duplicate sequence numbers...).

As per claim 15, Gambino and Johnson disclose all the subject matter as described above. In addition Gambino discloses the method, wherein stored security sequence values and node security sequence values are embedded in at least one header and/or at least one payload of a data packet that conforms to IPsec standards (col. 4 lines 45-50 and col. 3 lines 60-67; a header transport/THDR containing sequence number...RTP).

As per claim 16, Gambino and Johnson disclose all the subject matter as described above. In addition Gambino discloses the apparatus, wherein said stored security sequence value is periodically refreshed with a value at a selected interval from security sequence values already used in a secured communication session (col. 4 lines 24-41).

As per claim 30, Gambino and Johnson disclose all the subject matter as described above. In addition Gambino discloses the method, said storing further comprising periodically refreshing said saved client security sequence value with a number that is greater in value

than client security sequence values that have already been sent to said server device in a communication session (col. 4 lines 24-41).

As per claim 38 Gambino discloses all the subject matter as described above. Gambino reestablishes the communication by sending a replay message, for the resynchronization request, that includes remote system's resynchronization value.

Gambino does not explicitly teach response further includes a second resynchronization value (the replay message including resynchronization value sent from data host).

However Johnson discloses response further includes a second resynchronization value (Johnson col. 2 lines 18-60; establishing communication and exchanging multicast message between sender node and receiver node. The multicast message is structured to include a sequence number. When a node fails or sequence number is out of order a resynchronization request is sent from receiver node to sender node and the sender node acknowledges by sending its new marker/server resynchronization value and the sequence number of the last multicast message unacknowledged by the receiving node/negative acknowledgment multicast messages, messages receiver node has not received, sent from receiver node/resynchronization value).

Therefore it would have been obvious to one having ordinary skill in the art at the time of the invention was made to employ the teachings of Johnson within the system of Gambino because they are analogous in multi-computer synchronization and resynchronization method. One would have been motivated to incorporate resynchronization value of the requester along with resynchronization value of the server on acknowledgment/replay message for resynchronization request received because it is

Art Unit: 2136

well known in the art to include the requester resynchronization value. And also it would verify that the receiver is the right device that the requester intended to be resynchronized with.

As per claims 11, 26, and 34, Gambino and Johnson disclose all the subject matter as described above. In addition Gambino discloses the medium, further comprising instructions that, when executed by the processor, cause the processor to perform operations comprising reestablishing secured communication during a low-power state (col. 3 lines 63-65 and claim 7; data host failure is also low-power state. However applicant is advised to refer to Latka, patent number 5,646,996 on col. 6 lines 50-53 and col. 1 lines 10-14 and lines 56-67. Latka discloses detecting loss of synchronization, between transmitter and receiver of remote system, due to momentary power failure or a low battery condition and reestablishes communication by generating a communication sequence. It would have been obvious to one ordinary skill in the art at the time of the invention was made to modify low-power stage within the combination system of Gambino and Johnson because low-power stage causes data host failure/loss of data).

As per claims 12 and 27, Gambino and Johnson disclose all the subject matter as described above. In addition Gambino discloses the method, further comprising reestablishing secured communication while said first device lacks an active operating system and/or lacks an active microprocessor (col. 4 lines 34-37).

As per claim 19, Gambino and Johnson disclose all the subject matter as described above.

Art Unit: 2136

In addition Gambino discloses the resynchronizer, wherein at least one sender and at least one acknowledger are installed on any combination of server and client devices (col. 3 lines 29-32).

As per claim 23, Gambino and Johnson disclose all the subject matter as described above. In addition Gambino discloses the method further comprising storing said first resynchronization value in a nonvolatile storage medium (col. 4 lines 24-41).

As per claim 24, Gambino and Johnson disclose all the subject matter as described above. In addition Gambino discloses the method further comprising establishing secured communication using IPsec security standards (col. 4 lines 42-45).

As per claim 25, Gambino and Johnson disclose all the subject matter as described above. In addition Gambino discloses method further comprising resynchronizing said secured communication using said first resynchronization value to resynchronize secured data sent from said security interface and using said second resynchronization value to resynchronize secured data sent from said network node (claim 1; resynchronizing the communication by using data host (12) resynchronization value sent from data host (12) and resynchronization value replied from remote system to data host (12)).

As per claim 35, Gambino and Johnson disclose all the subject matter as described above. In addition Gambino discloses the method, further comprising reestablishing secured communication while the client device lacks an active operating system, lacks an active

Art Unit: 2136

microprocessor, or both (claim 12 lines 13-46; failure of data host/first data processing system and resynchronization of the first and second data processing system...).

Conclusion

6. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

Sydon et al. Patent NO.: US 6,466,800 B1 for resynchronizing, when desynchronization occurs, in using sequence values stored on nonvolatile memory/RAM, and

Jung Pub. No.: US 2001/0052072 A1, for resynchronizing communications that is out of synchronization in using sequence number and IP security.

7. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Eleni A. Shiferaw whose telephone number is 571-272-3867. The examiner can normally be reached on Mon-Fri 8:00am-5:00pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Ayaz R. Sheikh can be reached on 571-272-3795. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2136

Page 23

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Panay Examiner
AD 2131
9/27/05